

Options & Accessories



Choose from 21 exterior colors as well as custom colors. All meet AAMA 2605 test specifications. (Wood exteriors are also available.)




Wood interiors are available in seven species or prefinished white.




Printing limitations prevent exact color and wood species duplication. See your Andersen supplier for actual color and wood species samples.



Aluminum threshold is available in three finishes: brass anodized, bronze anodized or mill finish.



Full divided light, simulated divided light, removable interior grilles and Finelight™ grilles-between-the-glass are available. Choose from standard patterns or custom designs.



5-3/4" intermediate rail can be added to facilitate mounting of exit hardware.

Architectural Entry Doors

Featuring beautiful real wood panels and a low-profile threshold, these doors are ideal for light-commercial, institutional or even residential applications with accessibility requirements. They provide design flexibility for coordinating with other Andersen® products or for creating a unique architectural expression. Best of all, they're backed by the most trusted name in the window and door industry: Andersen.

Accessibility

Low-profile aluminum thresholds with 1/2" height meet accessibility requirements. Commercial doors also feature a 12" bottom rail.

Hardware*

Accepts standard commercial closer, panic bar, kick plate and hardware systems from most manufacturers.

Glazing Options

High-Performance™ Low-E4® and High-Performance Low-E4 Sun glass deliver optimum insulating performance and match other Andersen® products. Tempered glass is standard. Other options include laminated glass, patterned glass (obscure, pebble, cascade, fern and reed) and decorative insulating art glass.

Transoms and Sidelights



Both are available in standard and custom sizes, and in a variety of shapes to complement any entry door.

Owner-2-Owner® Limited Warranty

Glass is covered for 20 years and non-glass parts are covered for five years. Coverage is not pro-rated and is completely transferable between owners.






* Sold separately.



Standard Door and Sidelight Sizes

	Unit Number	Unit Dimension	
		Width	Height
Commercial Doors – Full Light			
	COM1-S	3'-1 5/8"	6'-10"
	COM1-B	3'-1 5/8"	7'-1 5/16"
	COM1-E	3'-1 5/8"	7'-11"
	COM-NY-7	3'-9 7/8"	7'-1 5/16"
	COM-NY-8	3'-9 7/8"	7'-11"
	COMDBL3-S	6'-2 3/4"	6'-10"
	COMDBL3-B	6'-2 3/4"	7'-1 5/16"
	COMDBL3-E	6'-2 3/4"	7'-11"

Single Door Hinge Orientations






- Left- or Right-Hinged
- Stationary

	Unit Number	Unit Dimension	
		Width	Height
Fixed Commercial Sidelights – Full Light			
	COMF14-S	1'-3 7/8"	6'-10"
	COMF14-B	1'-3 7/8"	7'-1 5/16"
	COMF14-E	1'-3 7/8"	7'-11"
	COMF24-S	2'-1 5/8"	6'-10"
	COMF24-B	2'-1 5/8"	7'-1 5/16"
	COMF24-E	2'-1 5/8"	7'-11"
	COMF30-S	2'-7 5/6"	6'-10"
	COMF30-B	2'-7 5/6"	7'-1 5/16"
	COMF30-E	2'-7 5/6"	7'-11"
	COMF32-S	2'-9 5/8"	6'-10"
	COMF32-B	2'-9 5/8"	7'-1 5/16"
	COMF32-E	2'-9 5/8"	7'-11"
	COMF36-S	3'-1 5/8"	6'-10"
	COMF36-B	3'-1 5/8"	7'-1 5/16"
	COMF36-E	3'-1 5/8"	7'-11"

	Unit Number	Unit Dimension	
		Width	Height
Commercial Doors with Intermediate Rail			
	COMH1-S	3'-1 5/8"	6'-10"
	COMH1-B	3'-1 5/8"	7'-1 5/16"
	COMH1-E	3'-1 5/8"	7'-11"
	COMH-NY-7	3'-9 7/8"	7'-1 5/16"
	COMH-NY-8	3'-9 7/8"	7'-11"
	COMHDBL3-S	6'-2 3/4"	6'-10"
	COMHDBL3-B	6'-2 3/4"	7'-1 5/16"
	COMHDBL3-E	6'-2 3/4"	7'-11"

Double Door Hinge Orientations

- Active/Active

	Unit Number	Unit Dimension	
		Width	Height
Fixed Commercial Sidelights with Intermediate Rail			
	COMHF14-S	1'-3 7/8"	6'-10"
	COMHF14-B	1'-3 7/8"	7'-1 5/16"
	COMHF14-E	1'-3 7/8"	7'-11"
	COMHF24-S	2'-1 5/8"	6'-10"
	COMHF24-B	2'-1 5/8"	7'-1 5/16"
	COMHF24-E	2'-1 5/8"	7'-11"
	COMHF30-S	2'-7 5/6"	6'-10"
	COMHF30-B	2'-7 5/6"	7'-1 5/16"
	COMHF30-E	2'-7 5/6"	7'-11"
	COMHF32-S	2'-9 5/8"	6'-10"
	COMHF32-B	2'-9 5/8"	7'-1 5/16"
	COMHF32-E	2'-9 5/8"	7'-11"
	COMHF36-S	3'-1 5/8"	6'-10"
	COMHF36-B	3'-1 5/8"	7'-1 5/16"
	COMHF36-E	3'-1 5/8"	7'-11"

Andersen® Architectural Commercial Door Performance Data

	Performance Rating	ASTM E330*
Operating Doors – Outswing	60 PSF (DP40)	3'-9 7/8" x 7'-11"
	82.5 PSF (DP55)	3'-1 5/8" x 7'-11"
	52.5 PSF (DP35)	6'-2 3/4" x 7'-11"
	75 PSF (DP50)	6'-2 3/4" x 7'-11"
Vertical Rod Panic Hardware Flushbolts in Lock Stiles		
	Performance Rating	AAMA/WDMA/CSA 101/I.S.2/A440-05
Fixed Outswing Door or Sidelight	DP 70	FD-C 70 3'-9 7/8" x 7'-11"
	DP 55	FD-C 55 6'-2 3/4" x 7'-11"

* This test method is contained within the AAMA/WDMA/CSA 101/I.S. 2/A440-05 standard that relates to structural performance. Air and water performance are not included.

Note: If a single Performance Rating DP is shown, the number represents both the positive and negative (+/-) Design Pressure rating for the product. This data is accurate as of October 17, 2007. Due to ongoing product changes, updated test results or new industry standards, this data may change over time. Call your Andersen representative for current performance information or upgrade options.